


LUMENLINEAR™ SYMMETRIC

ANOTHER LUMENRAIL® COMPONENT FOR LIFE SAFETY AND LIGHT.

Our linear product is a state-of-the-art, low-voltage LED light fixture that provides exceptional lighting performance to enhance any stairway, ramp or walkway application. Its soft light provides ample illumination for safety and ambiance without the glare or harshness of overhead lighting. Available with warm, neutral or cool white color temperatures, and a range of solid color options for static hues. Standard, mid and high output offerings make Lumenlinear a highly flexible and practical solution for adding beauty and light to your life safety installations.



- Industry leading output:
 - 60° and 120° symmetric beam spreads
- Matte and transparent lens options
- Available in:
 - 152, 284 or 413 lpf (4000 °K Values)
- IES full cutoff classification when installed in Wagner Architectural Systems hand rail
- Fully gasketed, extruded aluminum housing
- ETL wet location listed, UL1598 certified
- 5 year warranty
- Cast 316 stainless steel, mechanical mounting
- CCT standard in 5 white options
- 4 solid color options including wildlife amber
- Up to 88 CRI standard, 95+ available upon request
- 14 standard lengths from 6" to 80"

LUMENLINEAR™ SYMMETRIC

PROJECT NAME: _____

REP AGENCY: _____

APPROX. LINEAR FT. _____



SCAN QR CODE
for technical information, downloads, instructions,
and system configuration guides




LUMENLINEAR™
ANOTHER
LUMENRAIL®
COMPONENT
FOR LIFE SAFETY
AND LIGHT.


PART NUMBER BUILDER

LULS30K40120TS18	LULS						
EXAMPLE	FIXTURE TYPE	COLOR TEMP	FIXTURE WATTAGE	BEAM ANGLE	LENS OPTION	LENGTH NOMINAL - ASSEMBLED	
LULS	27K - 2700°K	BLU - Blue	20 - 1.85 W/FT	70° - 70° Spread	TS - Transparent	6 - 7.64"	48 - 48.95"
Lumenrail Linear	30K - 3000°K	GRN - Green	40 - 3.57 W/FT	120° - 120° Spread	Symmetric	12 - 13.51"	54 - 54.89"
	35K - 3500°K	RED - Red	60 - 5.45 W/FT		MS - Matte	18 - 19.39"	60 - 60.83"
	40K - 4000°K	AMB - Wildlife			Symmetric	24 - 25.33"	66 - 67.20"
	50K - 5000°K	Amber				30 - 31.23"	72 - 73.20"
						36 - 37.14"	78 - 79.20"
						42 - 43.07"	84 - 85.20"

ELECTRICAL SPECIFICATIONS


 All electrical connections to be made by a qualified electrician in accordance with all national, state and local electrical codes.	24VDC	ETL LISTED WET, UL 1598/CSA 22.2	0-10V INPUT (PWM)	-40°F TO +120°F
	INPUT VOLTAGE	CERTIFICATIONS	DIMMING	OPERATING TEMP
CLASS 2 REQUIRED	5 YEARS	UP TO 77 LM/W LED	UP TO 88 (95+ AVAIL. UPON REQUEST)	
DRIVER	WARRANTY	EFFICIENCY	CRI	

CONSTRUCTION



An extruded aluminum housing and fully gasketed assembly insure heat dissipation and ingress protection to IP67. Stainless steel hardware and mechanical attachment promote easy installation and longevity

PHOTOMETRICS



The symmetric output can be specified in narrow (70°) or industry leading wide (120°) beam spreads. Installed in Wagner Lumenrail®, Lumenlinear achieves full IES cutoff. Reports to view or download are available by scanning the QR code or visiting our website.

LUMENGEAR™ - LED DRIVER & NEMA ENCLOSURE OPTIONS

Wagner offers multiple ETL listed options for both 24VDC power supplies and NEMA enclosures. Quantities and types will be configured based on your specifications and design. Additional specification options are available by request. Not all options apply to all products, please verify compatibility with the factory.

CLASS II DRIVERS:

- *STD 100W Non Dim
- 0-10V (PWM)
- Multiple Wattages
- 24VDC

NEMA ENCLOSURES:

- 4X, 6
- LUMENPOST™:
Integrated 100W,
0-10V DIM

Specifications may change without prior notice, verify data at time of order, all rights reserved