

# LUMENRAIL® QUOTATION REQUEST FORM

Completion of this form, and providing us with highlighted drawings, has proven to greatly reduce our turn-around time on quotation requests. **Your assistance is greatly appreciated.**

Request Date: \_\_\_\_\_ Quotation Due Date: \_\_\_\_\_  
 Company Name: \_\_\_\_\_ Contact Name: \_\_\_\_\_  
 Email: \_\_\_\_\_ Phone: \_\_\_\_\_  
 Project Name: \_\_\_\_\_ Project Location: \_\_\_\_\_  
 Status:  Budget  Hard Bid Date Req'd On Site: \_\_\_\_\_  
 Specifier: \_\_\_\_\_ Specifier Contact Name: \_\_\_\_\_

**Approx Linear Footage:**  Illuminated Rail \_\_\_\_\_  Non-Illuminated Rail \_\_\_\_\_  No Handrail, Lighting Quote Only.

**Lumenlinear™ Fixture Specification - LULS** (Color, Control, Wattage, Distribution and Lens Finish)

**Select One CCT:**

2700°K  3000°K  3500°K  4000°K  5000°K  Amber  Blue  Green  Red

**Select Dimming:**

Yes  No

**Select One Wattage:**

2 Watts/FT  4 Watts/FT  6 Watts/FT

**Select One Distribution Combination:**

70° Symmetric  120° Symmetric  Asymmetric (45° above nadir)

**Select One Lens Finish:**

Matte  Transparent

**Lumenpod® 16 Fixture Specification - LULF** (Color, Control, Distribution)

**Select one CCT:**

2700°K  \*3000°K  \*4000°K  5000°K  Amber  Blue  Green  Red

**Select Dimming:**

Yes  No

**Select One Drive Current:**

350 mA  500 mA

**Select One Distribution Optic:**

16°  23°  46°  70°  94°

**Lumenpod® 28 fixture specification - LULR** (Color, Control, Distribution)

**Select One CCT:**

2700°K  \*3000°K  \*4000°K  5000°K  Amber  Blue  Green  Red

**Select Dimming:**

Yes  No

**Select One Drive Current:**

350 mA  500 mA

**Select One Distribution Optic:**

Symmetric  Asymmetric

**Handrail material specification** (Metal Alloy, Outside Diameter, and Finishlength)

**Select one Stainless Steel Material :**

304 Stainless Steel  316 Stainless Steel

**Select One Diameter:**

1.50" OD  1.66" OD  1.90" OD

**Select One Finish:**

#4 Satin, Circumferential Brushed  
 #4 Satin, Longitudinal Brushed +\$  
 #7 Brite, Polished +SS

OR

**Select Aluminum Material :**

6063 Aluminum

**Select One Diameter:**

1.90" OD  1.66" OD (wall mount only)

**Select One Finish:**

Clear Anodized (Silver)  
 Bronze Anodized (Duranodic)

Standard 100 Watt Driver & NEMA Enclosures included on quote. Quantity based on design, wattage and/or spacing.  
 Alternate listed driver and enclosure options are available if requested. Please contact us for specific options.